

**IN THE CLAIMS:**

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please CANCEL claims 25-26, and AMEND claims 14, 17, 21, 29, and 32 in accordance with the following:

14. (Currently amended) A gateway telecommunication device, comprising:

a first port to connect said device to a circuit switched telecommunication network;

a second port to connect said device to a packet based telecommunication network;

means for initiating and receiving calls for a user located in a home or office location where said device is also located;

means for said user to interface with said device without using a telecommunication network;

means in said device for executing requests from said user to initiate calls to parties on the circuit switched network or the packet based telecommunication network; ~~and~~

a single channel gateway means in said device for establishing a path between said first port and said second port inside said device in response to a request from a server on the packet based telecommunication network that is separate from a calling device that a caller at a remote location is using, and the server is acting on behalf of the caller at the remote location; and

means for responding to said request by connecting said second port directly to said caller at the remote location via the packet based telecommunication network,

whereby the gateway telecommunication device can serve as part of a distributed gateway system between said packet based telecommunication network and said circuit switched telecommunication network for said caller and whereby the device increases the

capacity of said distributed gateway system.

15. (Previously presented) A gateway telecommunication device according to claim 14, further comprising a third port to connect a conventional telephone apparatus via said device to said first port.

16. (Previously presented) A gateway telecommunication device according to claim 14, further comprising a mechanism to automatically connect said third port directly to said first port in the event of power failure.

17. (Currently amended) A system for telecommunication utilizing both a circuit switched telecommunication network and a packet based telecommunication network, comprising:

multiple gateway telecommunication devices each device having

- a first port to connect said device to a circuit switched telecommunication network;
- a second port to connect said device to a packet based telecommunication network;
- means for initiating and receiving calls for a user located in a home or office location where said device is also located;
- means for said user to interface with said device without using a telecommunication network;
- means in said device for executing requests from said user to initiate calls to parties on the circuit switched network or the packet based telecommunication network; and
- a single channel gateway means in said device for establishing a path between said first port and said second port inside said device in response to a request from a server on the packet based telecommunication network that is separate from a calling device that a caller at a remote location is using, and the server is acting on behalf of the caller at the remote

location; and

means for responding to said request by connecting said second port directly to said caller at the remote location via the packet based telecommunication network,

whereby the gateway telecommunication device can serve as part of a distributed gateway system between said packet based telecommunication network and said circuit switched telecommunication network for said caller and whereby the device increases the capacity of said distributed gateway system.

18. (Previously presented) A system for telecommunication according to claim 17, further comprising:

gateway location servers connected to said packet based telecommunication network, said gateway location servers being adapted to receive a request from a first gateway telecommunication device connected to said packet based telecommunication network for telecommunication with a specified telephone apparatus on said circuit switched telecommunication network, and further being programmed to select a second of said gateway telecommunication devices to serve as a gateway between said networks for said requested connection, and to forward said request to said second gateway telecommunication device via said packet based telecommunication network.

19. (Previously presented) A system for telecommunication according to claim 17, wherein the packet based telecommunication network comprises the Internet.

20. (Previously presented) A system for telecommunication according to claim 18, wherein the packet based telecommunication network comprises the Internet.

21. (Currently amended) A system for telecommunication according to claim 18,

wherein each of said gateway telecommunication devices includes means for registering with said gateway location servers the availability of said device to act as a gateway between said packet based network and said circuit switched network.

22. (Previously presented) A system for telecommunication according to claim 21, wherein each of said registered gateway telecommunication devices includes means for automatically notifying said gateway location servers when its PSTN connection is Off Hook so it temporarily is not available to serve as a gateway between the packet based network and the circuit switched network.

23. (Previously presented) A gateway telecommunication device according to claim 14, further comprising means for registering at said server the availability of said device to act as a gateway between said first port and said second port.

24. (Previously presented) A system for telecommunication according to claim 17, further comprising means for registering at said server the availability of said device to act as a gateway between said first port and said second port.

25. (Canceled)

26. (Canceled)

27. (Previously presented) A system for telecommunication utilizing both a circuit switched telecommunication network and a packet based telecommunication network, comprising:

multiple gateway telecommunication devices each device having

a first port to connect said device to a circuit switched telecommunication network;  
a second port to connect said device to a packet based telecommunication network;  
means for initiating and receiving calls for a user located in a home or office location  
where said device is also located;

means for said user to interface with said device without using a telecommunication  
network;

means in said device for executing requests from said user to initiate calls to parties on  
the circuit switched network or the packet based telecommunication network; and

a single channel gateway means in said device for establishing a path between said first  
port and said second port inside said device in response to a request from a server on the  
packet based telecommunication network that is separate from a calling device that a caller at a  
remote location is using, and the server is acting on behalf of the caller at the remote location;  
and

a gateway location server connected to said packet based telecommunication network  
having information of the location of said gateway telecommunication devices, said gateway  
location server being adapted to receive a request from a caller anywhere on said packet based  
telecommunication network for telecommunication with a specified telephone apparatus on said  
circuit switched telecommunication network, and further being programmed to select one of said  
gateway telecommunication devices to serve as a gateway between said networks for said  
requested connection, and to forward said request to said one gateway telecommunication  
device via said packet based telecommunication network.

28. (Previously presented) A system for telecommunication according to claim 27,  
wherein the packet based telecommunication network comprises the Internet.

29. (Currently amended) A system for telecommunication according to claim 27, wherein

each of said gateway telecommunication devices includes means for registering with said gateway location servers the availability of said device to act as a gateway between said packet based network and said circuit switched network.

30. (Previously presented) A system for telecommunication according to claim 29, wherein each of said registered gateway telecommunication devices includes means for automatically notifying said gateway location servers when its PSTN connection is Off Hook so it temporarily is not available to serve as a gateway between the packet based network and the circuit switched network.

31. (Previously presented) A system for telecommunication according to claim 27, wherein the circuit switched telecommunication network comprises a wireless cellular telecommunication network.

32. (Currently amended) A gateway telecommunication device according to claim 14 comprising:

a first port to connect said device to a circuit switched telecommunication network;  
a second port to connect said device to a packet based telecommunication network;  
means for initiating and receiving calls for a user located in a home or office location where said device is also located;

means for said user to interface with said device without using a telecommunication network;

means in said device for executing requests from said user to initiate calls to parties on the circuit switched network or the packet based telecommunication network; and

a single channel gateway means in said device for establishing a path between said first port and said second port inside said device in response to a request from a server on the

packet based telecommunication network that is separate from a calling device that a caller at a remote location is using, and the server is acting on behalf of the caller at the remote location,  
for use in a system for telecommunication having a circuit switched telecommunication network,  
a packet based telecommunication network, a plurality of said gateway telecommunication  
devices, and a gateway location server connected to said packet based telecommunication  
network having information of the location of said gateway telecommunication devices, said  
gateway location server being adapted to receive a request from a caller anywhere on said  
packet based telecommunication network for telecommunication with a specified telephone  
apparatus on said circuit switched telecommunication network, and further being programmed to  
select one of said gateway telecommunication devices to serve as a gateway between said  
networks for said requested connection, and to forward said request to said one gateway  
telecommunication device via said packet based telecommunication network,

whereby the gateway telecommunication device can serve as part of a distributed  
gateway system between said packet based telecommunication network and said circuit  
switched telecommunication network for said caller and whereby the device increases the  
capacity of said distributed gateway system.